



TS-832PX-4G

| CPU | AnnapurnaLabs Alpine AL324 ARM® Cortex-A57 4-core 1.7GHz processor |
|---|--|
| CPU Architecture | 64-bit ARM |
| Floating Point Unit | Yes |
| Encryption Engine | Yes |
| System Memory | 4 GB SODIMM DDR4(1 x 4 GB) |
| Maximum Memory | 16 GB (1 x 16 GB) |
| Memory Slot | 1 x SO-DIMM DDR4 |
| Flash Memory | 512 MB (Dual boot OS protection) |
| Drive Bay | 8 x 3.5-inch SATA 6Gb/s, 3Gb/s |
| Drive Compatibility | 3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives |
| Hot-swappable | Yes |
| | |
| M.2 Slot | Optional via a PCIe adapter |
| M.2 Slot SSD Cache Acceleration Support | Optional via a PCIe adapter Yes |
| SSD Cache Acceleration | |
| SSD Cache Acceleration Support 2.5 Gigabit Ethernet Port | Yes |
| SSD Cache Acceleration Support 2.5 Gigabit Ethernet Port (2.5G/1G/100M) | Yes 2 (2.5G/1G/100M/10M) |
| SSD Cache Acceleration Support2.5 Gigabit Ethernet Port (2.5G/1G/100M)10 Gigabit Ethernet Port | Yes 2 (2.5G/1G/100M/10M) 2 x 10GbE SFP+ |
| SSD Cache Acceleration Support2.5 Gigabit Ethernet Port (2.5G/1G/100M)10 Gigabit Ethernet PortWake on LAN (WOL) | Yes 2 (2.5G/1G/100M/10M) 2 x 10GbE SFP+ Yes |
| SSD Cache Acceleration Support2.5 Gigabit Ethernet Port (2.5G/1G/100M)10 Gigabit Ethernet PortWake on LAN (WOL)Jumbo Frame | Yes 2 (2.5G/1G/100M/10M) 2 x 10GbE SFP+ Yes Yes 1 |
| SSD Cache Acceleration Support2.5 Gigabit Ethernet Port (2.5G/1G/100M)10 Gigabit Ethernet PortWake on LAN (WOL)Jumbo FramePCIe Slot | Yes 2 (2.5G/1G/100M/10M) 2 x 10GbE SFP+ Yes Yes 1 Slot 1: PCIe Gen 2 x2 |

| LED Indicators | System Status, LAN, USB, HDD1~8 |
|---|---|
| Buttons | Power, Reset, USB Copy |
| Dimensions (HxWxD) | 188.2 × 329.3 × 280.8 mm |
| Weight (Net) | 6.38 kg |
| Weight (Gross) | 8.61 kg |
| Operating temperature | 0 - 40 °C (32°F - 104°F) |
| Storage Temperature | -20 - 70°C (-4°F - 158°F) |
| Relative Humidity | 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) |
| Power Supply Unit | 250W, 100-240V AC, 50/60Hz, 3.5A |
| Power Consumption: HDD Sleep Mode | 27.949 W |
| Power Consumption: Operating Mode, Typical | 50.858 W |
| Fan | System fan: 2 x 120mm, 12VDC CPU fan: 1 x 60mm |
| System Warning | Voice prompts or Buzzer |
| Kensington Security Slot | Yes |
| Max. Number of Concurrent Connections (CIFS) - with Max. Memory | 700 |

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting. * Sound Level Test

Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS. Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.